

ASUN245-P



245W Polycrystalline Photovoltaic Module

FULL
QMS

Quality Management System

- ✓ Raw material and module traceability
- ✓ Control of raw material
- ✓ Products manufacturing control
- ✓ Finished products inspection



- ✓ 100% finished modules flashed
- ✓ Flash report provided to customer
- ✓ 100% electroluminescence test



- ✓ 12-year material warranty
- ✓ Power output warranty:
 - 95% of the power on 5 years
 - 90% of the power on 12 years
 - 85% of the power on 18 years
 - 80% of the power on 25 years




- ✓ Error and Omission Insurance (Chubb Group): cover the economic loss sustained due to operational defects or performance failures



Factory certified

151W/m²



Certification:

- ✓ MCS
- ✓ IEC61215 & IEC61730
- ✓ Ammonia resistance
- ✓ Salt Mist corrosion resistance

Technical



Electrical Data

Maximum Power (Pmax)	245W
Tolerance	+ 5W
Maximum Power Voltage (Vpm)	29.6V
Maximum Power Current (Ipm)	8.28A
Open Circuit Voltage (Voc)	37.4V
Short Circuit Current (Isc)	8.73A
Cell efficiency	16.8%
Module efficiency	15.1%
Maximum System Voltage	1000V

STC: irradiation 1000W/m², AM 1,5 and temperature 25°C


Temperature Coefficient

NOCT	45°C +/-2%
Voltage Temperature (Voc)	-0.33%/°C
Current Temperature (Isc)	+0.06%/°C
Power Temperature (Pm)	- 0.44%/°C



Mechanical Data

Number of Cells	60 (6 x 10)
Cell Dimension	156*156mm
Bypass diodes	6
Glass Thickness	3.2mm
Maximum Load	5400Pa
Weight	21Kg
Dimensions	1650*990*50mm
Cable length / section	900mm / 4mm ²
Connectors	MC4 compatible
Operating Temperature	-40°C to +85°C




Frame

Built-in aluminium angle makes the frame stronger and reliable on long-term. Angle is set inside the frame cavity.



Back sheet

- Improved aesthetic appearance
- Anti-UV and Anti-Yellowing
- Ultimate moisture barrier
- Proven durability



Junction box

- IP65
- Fire resistance
- Excellent electrical insulation of components
- Stability and flexibility over a wide temperature range